



OCEAN SAFETY®



MED Ship's Wheel Approved LED lifebuoy light



datasheet

oceansafety.com

MED/SOLAS



0038/Y Y

Details

Features

- Colour – Light Yellow
- Colour – Bracket Black
- Light – Output 2 Candela minimum
- Light – Duration 2 hours min
- Light – Type Flashing LED
- Material – Lifebuoy Light Polypropylene Ether + PS
- Material – Bracket Polypropylene
- Storage Temperature -30° C to + 65° C
- Operating Temperature -1° C to + 30° C
- Storage Life 5 years
- Drop Height 76 metres
- Weight – Nominal 255 grams
- Battery Type Lithium Manganese Dioxide
- Activation Automatic via Pull Cord
- Approvals – Classification Societies SOLAS/MED

Transport Specification

- UN Hazard Code** : Exempt from transport packing, marking and labelling regulations under surface ADR & IMDG Special Provision 188, IATA Packing Instruction 970 Section II
- UN Proper Shipping Name** : Lithium metal batteries contained in equipment
- Packing Group** : II
- Lithium Content** : 0.54 g (Lithium metal battery)
- Watt hour rating** : 4.65 wh
- Labelling** : Packages must be labelled with the Lithium Battery Handling label

Description	Partnumber
APOLLO Lifebuoy light MED Ship's Wheel Approved	LBU0280

Your Life Saving Supplier

Ocean Safety Ltd, Saxon Wharf, Lower York Street, Southampton, SO14 5QF
 Tel: +44(0) 2380 720 800 Fax: +44(0) 2380 720 801
 www.oceansafety.com email: info@oceansafety.com