Helping to protect lives globally

Bird

BUILT BY **THE BEST** TO WITHSTAND THE WORST.

Product data sheet



JB08BA 4 x SCBA cabinet

EXPORT

CHAMPION

Typical use:

For the storage of 4 x Self contained 30-60 minute breathing apparatus. This cabinet is widely used in the Offshore energy sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The cabinet comes fitted with 1 central shelf and four plastic coated sprung clips to hold the SCBAs in place.

The door can be specified with left or right hinging and features a nylon rod handle to pull the door open to guarantee fast access even when wearing gloves.

future

Net Zero*

STANDARD

SOLUTION

PARTNER

Standard specification:

Dimensions (mm)

Height x width x depth: 1475 x 916 x 442

Aperture: 1234H x 699W

Internal depth: 388

35Kg Weight Kg:

Material specification:

Colour: Green RAL 6029

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: 316 Stainless steel

Handle: Nylon Rod

Seal: EPDM

Optional Extras:

Other RAL colours


Class 1 fire retardant composites

Perspex window with bezel

316 Stainless steel 3 way locking

Double doors

Manufactured in the UK



Reaister