

D Year

Guarantee

BUILT BY **THE BEST** TO WITHSTAND **THE WORST.**

Product data sheet

FOAM TROLLEY

EXTINGUISHER

JB65 Fire Extinguisher Cabinet

Typical use:

For the storage of 1 x Wheeled extinguisher (65 Kg max). This cabinet is widely used in the Offshore energy and marine sectors.

Description:

These cabinets are manufactured using Lloyds approved composites including UV resistant gelcoats to provide long lasting protection for equipment stored inside in even the harshest environments. This is backed up with an excellent IP rating of 56. It has both Lloyds and ABS approvals.

The design ensures a high level of rigidity for the relatively low weight with a very effective EPDM seal around the door aperture. The hinges are secured with 316 stainless steel nuts, bolts and washers.

The door can be specified with left or right hinging and features a Stainless Steel 'T' handle to pull the door open to guarantee fast access even when wearing gloves.

The cabinet features a reinforced flat floor to take the weight of a wheeled extinguisher.

Standard specification:

Dimensions (mm)

Height x width x depth: 1520 x 1005 x 912

Aperture: 1362H x 724W

Internal depth: 856

Weight Kg: 36 Kg

Material specification:

Colour: Red RAL3000

Material: Lloyds approved composites with UV stabilised gelcoat

Hinges: Stainless Steel

Handle: 316 Stainless steel 3-way locking 'T' handle

Seal: EPDM

Optional Extras:

Other RAL colours

Class 1 fire retardant composites

Perspex window with bezel

Heating and insulation

Manufactured in the UK



Jo Bird & Company Limited Factory lane, Bason Bridge, Highbridge, Somerset, TA9 4RN, United Kingdom I Tel: +44 (0) 1278 785546 | Email: info@jobird.co.uk | Web: jobird.co.uk

EXPORT

CHAMPION

